

CODE DIGIT 5 FEATURE		CODE	CODE DIGIT 6 FEATURE		CODE	CODE DIGIT 7 FEATURE				CODE
KENTROX	HARDWIRE	K	900:600/600:600 (1)	VOLTAGE LIMITING	1	SX LEADS TRMT & RCV				
	PLUG-IN	P				OPTIONAL (SX LEAD RCV & A&B LEADS TRMT) OR (SX LEAD TRMT & RCV)				
LENKURT		L	900:600/600:900/600:600 (2)		2	SX LEAD RCV & A&B LEADS TRMT				
TELLABS		T	600:900/600 (1)	OPTIONAL IMPEDANCE-FACILITY TO SWITCH	4	A&B LEADS TRMT & RCV				
TRANSCOM		R								
WESCOM	STANDARD	W	600:150/600/1200	4 WIRE	5				X	5
	HIGH DENSITY	Z		2 WIRE	7					
			150/600/1200:150/600/1200		6	LOOPBACK WITH OPTIONAL INTERNAL OR EXTERNAL CONTROL	NO		X	1
									X	2
			150/600/900/1200:600		3			X		3
							YES		X	4
CODE DIGIT 8										
REFERENCE 5 6 7 CODE										
KNTX CL K 15, 7 11 1										
KNTX P 15 11 1%										
LNKT L 14 11 3%										
TSCM R 12 15 4%										
TSL T 16 12 3%										
>WSCM Z 13, 4, 5 11, 3 2%										
WSCM W 10, 5 11 2%										
11, 3 11, 3, 4										
12 12										
14 11, 2, 4										

NOTES: (1) SEE DXM0 OR RCM4
(2) SEE RCM4

DESCRIPTION: REPEAT COILS & ADJUSTABLE PADS - 2 OR 4 WIRE